

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

LHM is a mineral-based lubricant fluid for specific use in brake systems, suspensions and vehicles equipped with a centralised hydraulic circuit. It is commonly used by ROLLS ROYCE and CITRÖEN, although not in all their models, and should only be used in vehicles with a green tank.

PROPERTIES

- High viscosity index.
- Very low freezing point.
- Great stability and excellent lubricating power.
- High protection against corrosion.

SPECIFICATIONS

UNE 26-090-88

TYPE ANALYSIS

PARAMETER	METHOD	UNIT	VALUE
Aspect	Visual	-	Clear green liquid
Density at 15°C	ASTM D7042	g/cm3	0,858
Viscosity at - 40°C (maximum)	UNE 26-382-88	cSt	2000
Viscosity at 100°C (minimum)	ASTM D7042	cSt	6,0
Boiling point	UNE 26-375-87	°C	>235
Flash point	UNE 51-023-90	°C	>110

The mentioned parameters represent typical values.

HOW TO USE

- Follow the vehicle manufacturer's instructions when adding or changing fluid.
- It should not be mixed with other fluids, nor used in conventional brake circuits.



PACKAGING

1 L
5 L
20 L
1000 L

Edition 2 Date: 16/06/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

TECHNICAL INFORMATION

STORAGE CONDITIONS AND EXPIRATION DATE

Store the product clean and dry in its original packaging, with the cap tightly closed to prevent moisture absorption.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

PRODUCT SAFETY

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.