

QUIMIBERICA, S.A.

BROOK'S SINTEX 2T - DISPENSER



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Synthetic oil for all types of 2-stroke engines lubricated by a mixture of oil and gasoline (direct or separate), air or water cooled. Use in tillers, lawnmowers, motorcycles, mopeds, chainsaws, etc.

PROPERTIES

- Its viscosity is suitable for all 2-stroke engines.
- Reduces smoke emissions.
- Facilitates instant start-up.
- Protects pistons, spark plugs and exhausts.
- Prevents pearl formation.
- Reduces the formation of carbon residues.
- Improves combustion.
- Increases power.
- Its medium dosage provides considerable savings when refuelling.

TYPE ANALYSIS

PARAMETER	UNITS	VALUE
Colour	-	Red
Density at 15°C	g/cm ³	0,882
Viscosity at 100°C	cSt	8,40
Viscosity index	-	110
Flash point	°C	125
Pour point	°C	-12

The characteristics mentioned represent typical values.

SPECIFICATIONS

JASO FD
API TC/ TSC-1, TSC-2, TSC-3
Motosierras y High Temperature Motor Bike Test Standard, TISI (low smoke) e ISO - L -EGD

HOW TO USE

Mix with gasoline, in a dosage between 2%-3%.



PACKAGING

1 L

Edition 1 Date: 10/03/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

QUIMIBERICA, S.A.

BROOK'S SINTEX 2T - DISPENSER



TECHNICAL INFORMATION

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

STORAGE CONDITIONS AND EXPIRATION

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

Edition 1 Date: 10/03/2026

Page 2

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.