



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

ANTIBULL - 12 is a long-lasting ORGANIC antifreeze-coolant liquid for closed circuits prepared at a 12% concentration. Recommended use in cooling circuits of light vehicles and large engines.

PROPERTIES

- Organic technology, multi-metal protection. It contains organic anticorrosive, antioxidant and antifoam additives, providing adequate protection for all parts in contact: aluminum block and components, thermostat, hoses, water pump, etc.
- Free of nitrites, amines, phosphates and silicates.
- Due to its anticorrosive properties, it protects all components used in the cooling systems of all types of engines.
- Compatible with gaskets and elastomers used in cooling systems.
- Protection against cavitation.
- Prevents the formation of limescale deposits as it is formulated with demineralized water.

SPECIFICATIONS

UNE 26361-88	MIL E/L 1415c	VOLVO
SAE J1034	VW TL 774 D/F (G12/G12+)	MB 326.3
ASTM D3306	FORD WSS M 97B44 D	AFNOR NF R15-601
ASTM D4985	MAN 324 TYPE SNF	BS 6580

TYPE ANALYSIS

PARAMETER	UNITS	VALUE
Colour	-	Pink, yellow and green
Density (20°C)	g/cc	1,01
Freezing point	°C	Max. -4
Boiling point in pressurized circuit (at 2,5 atm)	°C	Aprox. 115
pH	-	>7,5

The characteristics mentioned represent typical values

HOW TO USE

Before filling the circuit, the heat transfer fluid system must be completely emptied and rinsed with water to remove any particles that may have been deposited.

Use all year round.



PACKAGING

1 L
5 L
200 L
1000 L

Edition 5 Date: 27/03/2026

Page 1

This information is given as guidance and does not imply contractual liability. The technical data are average values and are subject to usual production fluctuations and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging.

Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defense of Consumers and Users (Royal Legislative Decree 21/2007) as long as the storage conditions are met. specified in this technical sheet. This technical sheet specifies the duration of said product warranty.

Avda. de Cameros, Parc. 183- Tel.: +34 941 25 66 11- Fax: +34 941 24 15 89 -26151 Arrúbal (La Rioja)- SPAIN

quimiberica@quimiberica.es - www.quimiberica.es - ISO 9001 – ISO 14001 – ISO 45001



TECHNICAL INFORMATION

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, sources of heat, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

PRODUCT SAFETY



Warning:

- H373 May cause damage to organs through prolonged or repeated exposure.

Contains: ethanediol, ethylene glycol.

“Always follow the information on the product label”.