

BROOK'S 10W30 STOU



Manufactured in QUIMIBERICA,S.A.

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Multifunctional lubricant for use in engines, transmissions, wet brake systems and integral hydraulic systems of diesel and gasoline agricultural tractors.

PROPERTIES

- Its additives allow for greater lubricant flow and energy transmission throughout the system to ensure proper operation.
- It reduces wear on cams and liners and prolongs the useful life and durability of the engine.
- It offers high performance and protection in both conventional gearboxes and new variable transmissions for tractors.
- Simplicity in maintenance, a single oil for the entire tractor.

SPECIFICATIONS

JOHN DEERE J27
MASSEY FERGUSON CMS 1145, 1144, 1139
FORD M2C159B
API CE, CF, CF-4, CG-4, SF
CATERPILLAR TO-2
ZF TE ML 06A, 06B, 06C, 06D, 07B

ALLISON C4
API GL-4
ACEA E2
MAN 271
MB 227.1, MB 228.1
MIL-L-2104D

TYPE ANALYSIS

PARAMETER	METHOD	UNIT	VALUE
Aspect	Visual	-	Amber
Density at 15°C	ASTM D7042	g/cm3	0,865
Viscosity at 100°C	ASTM D7042	cSt	9,3-12,5
Viscosity index	ASTM D2270	-	146
Flash point	ASTM D92	°C	226
Pour point	ASTM D97	°C	-27
TBN	ASTM D2896	mg KOH/g	11,7

The mentioned parameters represent typical values.



PACKAGING

5 L
20 L
50 L
200 L
1000 L

Edition 2 Date: 25/06/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

Avda. de Cameros, Parc. 183- Tel.: +34 941 25 66 11 - 26151 Arrúbal (La Rioja)- SPAIN
quimiberica@quimiberica.es - www.brookslubricantes.es - ISO 9001 – ISO 14001 – ISO 45001

TECHNICAL INFORMATION

STORAGE CONDITIONS AND EXPIRATION DATE

Store the product clean and dry in its original packaging, with the cap tightly closed to prevent moisture absorption.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

PRODUCT SAFETY

- EUH208 - Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.
- EUH208 - Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts. May produce an allergic reaction.
- EUH208 - Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

“Always follow the information on the product label”.