



### TECHNICAL INFORMATION

#### DESCRIPTION AND APPLICATION

Industrial hydraulic oil formulated from mineral bases and a complex set of additives, which improve the properties of the base oils, making them optimal for any hydraulic system, extending their duration and use.

#### PROPERTIES

- It has anticorrosive properties.
- Antifoaming properties and demulsifying properties, which prevent the formation of highly viscous emulsions that can damage valves and pumps.
- Antioxidant properties.
- Contains anti-wear additives.

#### SPECIFICATIONS

DIN 51524 part I (HL)

AFNOR NFE 48603

ISO 6743-4 (HL)

#### TYPE ANALYSIS

PARAMETERS	UNITS	VALUE				
ISO GRADE	-	22	32	46	68	100
Viscosity at 40°C	cSt	22	34	46	63	94
Minimum viscosity index	-	95				
Minimum flash point	°C	200				
Minimum pour point	°C	-9				

The characteristics mentioned represent typical values.

#### STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, sources of heat, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

#### PRODUCT SAFETY

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.



#### PACKAGING

5 L  
10 L  
20 L  
50 L  
200 L  
1000 L

Edition 1 Date: 10/03/2026

Page 1