



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Industrial hydraulic oil formulated from highly refined paraffinic mineral bases and a complete set of E.P (**EXTREME PRESSURE**) additives that improve the properties of the base oils, making them optimal for any hydraulic system, extending their duration and use. Special oil for controlled hydrostatic circuits and systems with special thermal characteristics. And for hydraulic systems and pumps that require special anti-wear behavior.

PROPERTIES

- Low freezing point.
- High viscosity index.
- Gasket compatible.
- Good antifoam properties.
- Excellent anti-wear properties for extreme pressure work.

SPECIFICATIONS

DIN 51524 part III y II	ISO 11158
DENISON HF-0, HF-1, HF-2	ISO 6743-4 HV
VICKERS M 2950-S / I 286-S	AFNOR E 48603 HV
CINCINNATI P-68 (ISO 32); P-69(ISO-68); P70(ISO-46)	

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE		
ISO GRADE	-	32	46	68
Viscosity at 40°C	cSt	34	46	63
Minimum viscosity index	-	140		
Minimum flash point	°C	180		
Minimum pour point	°C	-30		

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, sources of heat, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 L
50 L
200 L
1000 L
BULK

Edition 1 Date: 10/03/2026

Page 1

This information is given as guidance and does not imply contractual liability. The technical data are average values and are subject to usual production fluctuations and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging.

Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defense of Consumers and Users (Royal Legislative Decree 21/2007) as long as the storage conditions are met, specified in this technical sheet. This technical sheet specifies the duration of said product warranty.

Avda. de Cameros, Parc. 183- Tel.: +34 941 25 66 11- Fax: +34 941 24 15 89-26151 Arrúbal (La Rioja)- SPAIN

quimiberica@quimiberica.es - www.quimiberica.es - ISO 9001 – ISO 14001 – ISO 45001

QUIMIBERICA, S.A.

BROOK'S HIDRAK HVLP



BROOK'S

TECHNICAL INFORMATION

PRODUCT SAFETY

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008. In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

Edition 1 Date: 10/03/2026

Page 2

This information is given as guidance and does not imply contractual liability. The technical data are average values and are subject to usual production fluctuations and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging.

Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defense of Consumers and Users (Royal Legislative Decree 21/2007) as long as the storage conditions are met. specified in this technical sheet. This technical sheet specifies the duration of said product warranty.

Avda. de Cameros, Parc. 183- Tel.: +34 941 25 66 11- Fax: +34 941 24 15 89-26151 Arrúbal (La Rioja)- SPAIN

quimiberica@quimiberica.es - www.quimiberica.es - ISO 9001 – ISO 14001 – ISO 45001