



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Long-lasting synthetic lubricant (Long Life) for petrol and diesel engines without particle filters. It is suitable for both normal and very severe conditions of use (city, sports driving, repeated starts, motorway, etc.) and at any time of year.

PROPERTIES

- Protection and optimal operation of 3-way catalytic converters, preventing clogging.
- Facilitates starting at low temperatures.
- High resistance to wear in the most severe conditions.
- High resistance to oxidation and minimal formation of sludge and residue, facilitating engine cleaning and durability.
- Especially recommended for high-power passenger cars.
- Its composition allows for longer oil change periods and minimises lubricant consumption.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Density at 15°C	g/cm ³	0,852
Viscosity at 100°C	cSt	12,5-16,3
Viscosity index	-	160
Flash point	°C	231
Pour point	°C	-39

The characteristics mentioned represent typical values.

SPECIFICATIONS

ACEA A3/B4	MB 229.5
API SN/CF	RENAULT 0700/0710
VW 502.00/505.00	PORSCHE A40
BMW-LL01	

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

1 L
5 L

Edition 1 Date: 21/01/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

QUIMIBERICA, S.A.

BROOK'S SAE 0W40



BROOK'S

TECHNICAL INFORMATION

PRODUCT SECURITY

EUH208-Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts. May produce an allergic reaction.

“Always follow the information on the product label”.

Edition 1 Date: 21/01/2026

Page 2

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.