



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

High-performance **LOW SAPS** synthetic lubricant recommended for diesel and gas engines of heavy vehicles for road transport with extended change periods (**Long Life**). Designed for engines equipped with after-treatment systems such as diesel particulate filters (FAP or DPF). Especially adapted to Euro VI engines.

PROPERTIES

- It has extraordinary detergent, anti-oxidant and anti-corrosive properties that allow for extended drain intervals.
- It offers excellent thermal stability.
- LOW SAPS technology, low content of sulphated ash, phosphorus and sulphur.
- FUEL ECONOMY technology.

TYPE ANALYSIS

| PARAMETERS | UNITS | VALUE |
|--------------------|-------------------|----------|
| Density at 15°C | g/cm ³ | 0,848 |
| Viscosity at 100°C | cSt | 9,3-12,5 |
| Viscosity index | - | 148 |
| Flash point | °C | 242 |
| Pour point | °C | -33 |

The characteristics mentioned represent typical values.

SPECIFICATIONS

| | |
|-------------------------------|---|
| ACEA E6/E9-16 | RENAULT TRUCKS RLD-3 |
| ACEA E7/E8/E11-24 | VOLVO VDS-4.5 |
| API CK-4/SN | MACK EOS-4.5 |
| MAN M3775 | DEUTZ DQC IV-18 LA |
| JASO DH-2 | DETROIT DIESEL DDC 93K218/93K222/93K223 |
| CUMMINS CES 20081/20086/20087 | DAIMLER DTFR 15C100/110/120/130 |
| MTU Type 3.1 | CAT ECF-3 |

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 L
50 L
200 L
1000 L

Edition 1 Date: 10/03/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging.

Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

QUIMIBERICA, S.A.

BROOK'S SAE 10W30 HDD LONG LIFE



BROOK'S

TECHNICAL INFORMATION

PRODUCT SAFETY

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008. In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

Edition 1 Date: 10/03/2026

Page 2

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.