

QUIMIBERICA, S.A.

BROOK'S SAE 15W40 ENERGETIC E9



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Mineral lubricant designed for the latest generation EURO VI heavy duty diesel engines requiring API CK-4 quality level. Compatible with diesel engines equipped with exhaust gas recirculation (EGR) systems and with engines equipped with exhaust gas post-treatment systems (DPF, DOC, SCR, FAP).

PROPERTIES

- Excellent detergent, dispersant and anti-wear properties to keep the most sensitive parts of the engine clean, allowing control of sludge, soot and deposits.
- Its LOW SAPS technology protects engines that have systems such as particle filters.
- Optimal oxidation stability protecting the engine at high temperatures.
- Great adaptation to high temperatures to resist viscosity loss due to thermal and mechanical shear.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Density at 15°C	g/cm ³	0,867
Viscosity at 100°C	cSt	12,5-16,3
Viscosity index	-	135
Flash point	°C	> 200
Pour point	°C	< -27

The characteristics mentioned represent typical values.

SPECIFICATIONS

ACEA E9/E7	RENAULT RLD-3
API CK-4/SN	VOLVO VDS-4.5
MAN 3775	MACK EO-S 4.5
MB 228.31	CUMMINS CES 20086
CAT ECF-3	DEUTZ DQC III-18 LA
MTU Type 2.1	FORD WSS-M2C171-F1
DETROIT DIESEL DDC 93K222	

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 L
200 L
1000 L

Edition 1 Date: 10/03/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product warranty.

QUIMIBERICA, S.A.

BROOK'S SAE 15W40 ENERGETIC E9



TECHNICAL INFORMATION

PRODUCT SAFETY

EUH208-Contains coconut oil, reaction products with boric acid (H3BO3), diethanolamine and glycerol. May produce an allergic reaction.

EUH208-Contains calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate. May produce an allergic reaction.

EUH208-Contains 2,5-Furandione, polymer with 1-hexadecene, 2-methyloxirane polymer with oxirane bis(2-aminopropyl) ether and 2-methyl-1-propene, 4-(phenylamino)phenyl imide. May produce an allergic reaction.

EUH208-Contains alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic reaction.

"Always follow the information on the product label".

Edition 1 Date: 10/03/2026

Page 2

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.