

QUIMIBERICA, S.A.

BROOK'S SAE 5W20 EVOLUTION



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Synthetic lubricant for direct injection engines specially developed for engines with the latest generation **EcoBoost** technology. Designed to maximize fuel economy in hybrid, gasoline and diesel vehicles.

PROPERTIES

- It can be used when ACEA A1/B1 quality level is required.
- Compatible with engines that require Ford WSS-M2C-925B or WSS-M2C-913B specifications
- **FUEL ECONOMY.** Increases fuel economy (its friction modifiers reduce the loss of energy produced by contact between the metal parts of the engine) allowing emissions to be reduced.
- Its viscosity grade reduces internal friction and allows cold starts while maintaining perfect lubrication.
- Its low ash content (**LOW SAPS**) allows the operation of three-way catalytic converters and DPf devices to be optimised, extending their useful life.
- Provides an excellent level of cleanliness and extraordinary engine anti-wear protection.

TYPE ANALYSIS

PARAMETER	UNIT	VALUE
Density at 15°C	g/cm ³	0,848
Viscosity at 100°C	cSt	6,9-9,3
Viscosity index	-	154
Flash point	°C	236
Pour point	°C	-45

The mentioned parameters represent typical values.

SPECIFICATIONS

ACEA C5
API SN

FORD WSS-M2C-948-B
JAGUAR LAND ROVER ST JLR.03.5004



PACKAGING

1 L
5 L
20 L
50 L
200 L
1000 L

Edition 1 Date: 21/01/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

QUIMIBERICA, S.A.

BROOK'S SAE 5W20 EVOLUTION



TECHNICAL INFORMATION

STORAGE CONDITIONS AND EXPIRATION DATE

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

PRODUCT SAFETY

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

Edition 1 Date: 21/01/2026

Page 2

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.