

QUIMIBERICA, S.A.

BROOK'S SAE 5W40 A3/B4



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Synthetic lubricant developed for all petrol and diesel engines. Suitable for engines with turbochargers, multi-valves and direct injection. Lubricant compatible with engines equipped with catalytic converters and with engines using unleaded fuel or liquefied petroleum gas (LPG).

PROPERTIES

- Excellent protection against wear and fouling thanks to its rapid lubrication from start-up and its detergent and dispersant additives.
- Its low-temperature fluidity facilitates cold starts, and it also offers good resistance to higher temperatures.
- High resistance to oxidation, which allows for extended drain intervals.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Density at 15°C	g/cm ³	0,850
Viscosity at 100°C	cSt	12,5-16,3
Viscosity index	-	160
Flash point	°C	228
Pour point	°C	-36

The characteristics mentioned represent typical values.

SPECIFICATIONS

ACEA A3/B4	MB 229.3
API SN/CF	GM LL-B-025
VW 502.00/505.00	PSA B71 2296
RENAULT 0700/0710	PORSCHE A40
BMW LL-01	FIAT 9.55535.M2
CHRYSLER MS 12991	

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

1 L
5 L
20 L
50 L
200 L
1.000 L

Edition 1 Date: 21/01/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

QUIMIBERICA, S.A.

BROOK'S SAE 5W40 A3/B4



TECHNICAL INFORMATION

PRODUCT SECURITY

EUH208-Contains Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic reaction.

“Always follow the information on the product label”.

Edition 1 Date: 21/01/2026

Page 2

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.