



### TECHNICAL INFORMATION

#### DESCRIPTION AND APLICATION

Multigrade **Extreme Pressure** lubricating oil for gearboxes and differentials of cars, trucks, buses and agricultural equipment. Extreme pressure oil especially recommended for the lubrication of hypoid and helical type gearboxes and differentials and under-sump gears.

#### PROPERTIES

- Contains corrosion inhibitors on metals.
- Contains E.P. additives. and anti-wear that considerably increases the life of the equipment.
- Good antifoam and demulsifying properties.
- Good antioxidant properties, which prevent oxidation of the oil, preventing it from increasing viscosity and deteriorating.
- Compatible with gaskets and metal parts of manual transmission synchronizers.

#### TYPE ANALYSIS

PARAMETER	UNIT	VALUE
Density at 15°C	g/cm <sup>3</sup>	0,883
Viscosity at 100°C	cSt	13,5-18,5
Viscosity index	-	>95
Flash point	°C	>210
Pour point	°C	<-9

The characteristics mentioned represent typical values

#### SPECIFICATIONS

API GL-4, API GL-5, MT-1 y PG-2  
MIL-PRF-2105-E, MB235.0 level  
MAN 341 Type E2,Z2 /342 Type M2  
ZF TF-ML 2B, 5A, 7A, 12E, 16B, 17B, 19B, 21A

NATO O-226  
LIEBHERR  
SCANIA STO 1:0  
SAE J 2360

#### STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, sources of heat, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



#### PACKAGING

1 L  
5 L  
20 L  
50 L  
200 L  
1000 L  
BULK

Edition 1 Date: 10/03/2026

Page 1

# QUIMIBERICA, S.A.

## BROOK'S SAE 80W90 EP



BROOK'S

### TECHNICAL INFORMATION

#### PRODUCT SAFETY

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008. In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

Edition 1 Date: 10/03/2026

Page 2