

QUIMIBERICA, S.A.

CALCIUM GREASE



BROOK'S

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

CALCIUM GREASE is a calcium soap lubricating grease. Specially designed for general lubrication of vehicle joints and chassis, bearings, seals, gears and industrial machinery.

PROPERTIES

- Grease formulated from highly refined paraffinic and naphthenic mineral bases and calcium soap.
- Especially suitable in the presence of water or humidity for working at moderate temperatures, such as in pumps, ships and boats.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Color	-	Brown
NLGI Consistency	-	2
Penetration, 0.1 mm, 25 °C, unworked, ASTM D 217	-	265/295
Dropping point, ASTM D 2265	°C	90/95
Sphere of use	°C	-15 hasta +70

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 Kg
50 L
200 L

Edition 4 Date: 20/05/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging.

Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.