



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Developed for use in oil-filled electrical equipment including power and distribution transformers, rectifiers, circuit breakers and switchgear.

PROPERTIES

- Thanks to its low viscosity this standard grade offers extremely good heat transfer characteristics, ensuring that heat is removed efficiently.
- Formulated to offer good resistance to oil degradation, this grade also provides good oxidation stability for improved transformer life and minimal maintenance.
- Very good low temperature properties. Naphthenic characteristics allow the transformer to start at the lowest possible temperature, without using pour point depressants.
- Not inhibited.
- PCB free.

SPECIFICATIONS

IEC 60296

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Viscosity at 40°C	cSt	<12
Pour point	°C	<-40
Flash point	°C	>135
Dielectric breakdown voltage	kV	>30

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
200 L
1.000 L

Edition 9 Date: 07/11/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.