

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

ORGANIC antifreeze-coolant liquid for closed circuits prepared at 42% concentration. Recommended use in cooling circuits of light vehicles with very demanding characteristics, industrial vehicles and large engines that require severe **LONG LIFE** service. In any case follow the manufacturer's recommendations.

PROPERTIES

- **"Organic"** technology, multi-metal protection. It contains **organic** anticorrosive, antioxidant and antifoam additives, providing adequate protection for all parts in contact: aluminum block and components, thermostat, hoses, water pump, etc.
- Free of **nitrites, amines, phosphates and silicates**.
- Due to its anticorrosive properties, it protects all components used in the cooling systems of all types of engines.
- Compatible with gaskets and elastomers used in cooling systems.
- Protection against cavitation. Prevents the formation of bubbles, which promote corrosion and hinder heat transmission.
- Especially suitable for internal combustion engines, such as trucks, buses, public works machinery, passenger cars, whether gasoline or diesel, and radiators with aluminum components, where high temperature protection is very important.
- Prevents the formation of limescale deposits as it is formulated with demineralized water.

SPECIFICATIONS

UNE 26361-88
ASTM D3306
ASTM D4985
AFNOR NF R15-601
BS 6580
VW TL 774 F (G12+)
MB 325.3 / 326.3
MAN 324 Type SNF

DAF 74002
Scania TB 1451
MACK 014GS17004
Renault 41-01-001 Type D
PSA B71 5110
FORD WSS-M97B44-D
Opel/GM QL130100



PACKAGING

1 L
5 L
20 L
200 L
1000 L

STORAGE CONDITIONS AND EXPIRATION DATE

The product does not require special storage measures.

As general storage conditions, sources of heat, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

Edition 7 Date: 16/06/2026

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

TECHNICAL INFORMATION

HOW TO USE

Before filling the circuit, the heat transfer fluid system must be completely emptied and rinsed with water to remove any particles that may have been deposited.

Use all year round.

Do not add water.

TYPE ANALYSIS

PARAMETER	METHOD	UNIT	VALUE
Colour	Visual	-	Pink
Density at 20°C	ASTM D5931	g/cm ³	1,055
Freezing point	ASTM D97	°C	-26
Boiling point in pressurized circuit (at 2,5 atm)	ASTM D1120	°C	Approx. 170
pH	ASTM D1287	-	>7,5

The characteristics mentioned represent typical values.

PRODUCT SAFETY



Warning:

- H302 Harmful if swallowed.
- H373 May cause damage to organs through prolonged or repeated exposure.

Contains: ethanediol, ethylene glycol.

“Always follow the information on the product label”.