



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Industrial hydraulic oils formulated from highly refined paraffinic mineral bases and a complex set of additives, which improve the properties of the base oils, making them optimal for any hydraulic system, extending their life and use. Special oil for hydraulic circuits where viscosity variation with temperature must be minimal.

PROPERTIES

- Low freezing point.
- High viscosity index.
- Compatible with gaskets.
- Good anti-foaming properties.
- Marked anti-wear properties.

SPECIFICATIONS

DIN 51524 parte III
ISO 6743-4 HV
AFNOR E 48603 HV
VICKERS M 2950-S / I 286-S

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE		
ISO GRADE	-	32	46	68
Viscosity at 40°C	cSt	31	44	66
Minimum viscosity index	-	140		
Minimum Flash point	°C	200		
Minimum pour point	°C	-36		

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 L
50 L
200 L
1.000 L

Edition 5 Date: 16/02/2024

Pág. 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging.

Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.