

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Synthetic lubricant oil for automatic gearboxes. **A.T.F. Automatic Transmission Fluid.** High-performance hydraulic fluid for lubrication of automatic gearboxes and latest generation power steering. Can be used following the vehicle manufacturers' instructions.

PROPERTIES

- Protects against corrosion and wear.
- Has antioxidant properties.
- High viscosity index.
- Contains anti-friction additives

SPECIFICATIONS

DEXRON III H	Ford Mercon
ALLISON C-4	CAT TO-2
MB 236.1	ZF -TE-ML 04D, 11A, 14A , 17 C
Voith H55.6335xx	MAN 339 TYPE Z-1, V-1

TYPE ANALYSIS

	UNITS	VALUE
Aspect and color	-	Clear red liquid
Density at 15°C	g/cm ³	0,848
Viscosity at 100°C	cSt	6,3
Viscosity index	-	>180
Flash point	°C	217
Pour point	°C	-51

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

1 L
5 L
20 L
50 L
200 L
1000 L

Edition 11 Date: 31/10/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.