

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Universal lubricant for tractor transmissions (UTTO) developed for mechanisms that include hydraulic transmission, differential, wet brakes and oil-immersed clutches.

PROPERTIES

- Good anti-wear and extreme pressure properties ensure optimum protection of gears and hydraulic components.
- Eliminates vibrations and protects against friction in oil bath brakes.
- Good oxidation resistance and compatibility with seal materials.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Color	-	Amber
Density at 15°C	g/cm ³	0,864
Viscosity at 100°C	cSt	9,3-12,5
Viscosity index	-	130
Flash point	°C	>200
Pour point	°C	<-21

The characteristics mentioned represent typical values.

SPECIFICATIONS

JOHN DEERE JMD J20C/D

MASSEY FERGUSON CMS M 1135/1141/1143/1145

CNH MAT 3525/3526

KUBOTA UDT

VOLVO CE WB 101

CAT TO-2

ALLISON C-4

API GL-4

FORD ESN-M2C 134D

ZF TE-ML-03E/05F/06P/17E

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 L
50 L
200 L
1.000 L
BULK

Edition 6 Date: 06/11/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.