

QUIMIBERICA, S.A.

HIDRAK TRACTOR



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

High-performance universal lubricant for tractor transmissions (UTTO) developed for complex mechanisms including hydraulic transmission, differential, wet brakes and oil-immersed clutches.

PROPERTIES

- Excellent fluidity at low temperatures.
- Good anti-wear and extreme pressure properties, high load-bearing and lubricating capacity in all working regimes.
- Provides excellent protection against corrosion and rust, as well as high oxidation stability.
- Eliminates vibrations and protects against friction in brakes immersed in an oil bath.
- High resistance to foam formation, which reduces the formation of sludge, lacquers and varnishes.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Color	-	Amber, brown
Density at 15°C	g/cm ³	0,864
Viscosity at 100°C	cSt	9,3-12,5
Viscosity index	-	140
Flash point	°C	>200
Pour point	°C	<-39

The characteristics mentioned represent typical values.

SPECIFICATIONS

JOHN DEERE JDM J20C/D	CAT TO-2
MASSEY FERGUSON CMS 1135/1141/1143/1145	ALLISON C-4
CNH MAT 3525/3526	API GL-4
FORD ESN-M2C-134D	VOLVO CE WB 101

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.
As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.
Store closed containers between 5 and 35°C, in a dry and well-ventilated place.
Best before date: 2 years.



PACKAGING

5 L
10 L
20 L
50 L
200 L
1.000 L
BULK

Edition 9 Date: 06/11/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.