

QUIMIBERICA, S.A.

POWER STEERING



BROOK'S

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Lubricating oil for power steering and automatic transmissions (**A.T.F. Automatic Transmission Fluid**).
Use in power steering systems of cars and trucks. Severe services.

PROPERTIES

- Protects against corrosion and wear.
- Contains anti-friction additives
- Has antioxidant properties.
- High viscosity index.

SPECIFICATIONS

DEXRON II D	RENK
ALLISON C-4	CAT TO-2
MB 236.7/ MB 236.6	ZF -TE-ML 04D, 11A, 14A
Voith H55.6335xx	MAN 339 TYPE Z-1, V-1

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Aspect and color	-	Clear red liquid
Density at 15°C	g/cm ³	0,860
Viscosity at 100°C	cSt	5,5
Viscosity index	-	178
Flash point	°C	200
Pour point	°C	-39

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.
As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.
Store closed containers between 5 and 35°C, in a dry and well-ventilated place.
Best before date: 2 years.



PACKAGING

1 L
2 L
5 L
10 L
20 L
50 L
200 L
1000 L

Edition 10 Date: 31/10/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.