QUIMIBERICA, S.A.

PREMIUM

BROOK'S

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Industrial hydraulic oils formulated from highly refined paraffinic mineral bases and a complete set of additives, which improve the properties of the base oils, making them optimal for any hydraulic system, extending their life and use.

Special oil for hydraulic systems, reinforced for **work in extreme temperatures and conditions**.

PROPERTIES

- Contains corrosion inhibitors on metals, providing a protective film against corrosion.
- Good antioxidant properties, which prevent the oxidation of the oil, preventing it from increasing viscosity and deteriorating.
- Good anti-rust properties. Good stability to hydrolysis and good thermal properties.

TYPE ANALYSIS

	VISCOSITY AT 100ºC, cSt	VISCOSITY INDEX	FLASH POINT Mínimo, ºC	POUR POINT Minimum, ºC
SAE 10W PREMIUM	> 4,1	95	200	-9
SAE 20 PREMIUM	6,9 - 9,3			
SAE 30 PREMIUM	9,3 - 12,5			
SAE 40 PREMIUM	12,5-16,3			

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35ºC, in a dry and well-ventilated place.

Best before date: 2 years.

PACKAGING

5 L
20 L
50 L
200 L
1.000L