



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Industrial hydraulic lubricant for reciprocating compressors (piston), formulated from mineral bases and a complete set of additives that give them unique characteristics for EXTREME PRESSURE work.

PROPERTIES

- Excellent anti-foaming qualities.
- Good air removal capacity.
- High loading capacity.
- Minimal tendency to deposit formation.
- Excellent resistance to oxidation.
- High anti-rust power.

SPECIFICATIONS

DIN 51506 VDL

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE			
ISO GRADE	-	46	68	100	150
Viscosity at 40°C	cSt	46	63	94	146
Minimum viscosity index	-	95			
Minimum flash point	°C	200			
Minimum pour point	°C	-9			

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

20 L
50 L
200 L

Edition 6 Date: 07/11/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.