

QUIMIBERICA, S.A.

SAE 10W40 HDD LONG LIFE



BROOK'S

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

High-performance LOW SAPS synthetic lubricant recommended for diesel and gas engines of heavy vehicles for road transport. Designed for engines equipped with after-treatment systems such as diesel particulate filters (FAP or DPF). Especially adapted to Euro VI engines.

PROPERTIES

- It has detergent, anti-oxidant and anti-corrosive properties that allow for long oil change intervals.
- It offers excellent thermal stability.
- LOW SAPS technology, low content of sulphated ash, phosphorus and sulphur.
- FUEL ECONOMY technology.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Density at 15°C	g/cm ³	0,847
Viscosity at 100°C	cSt	12,5-16,3
Viscosity index	-	155
Flash point	°C	236
Pour point	°C	- 30

The characteristics mentioned represent typical values.

SPECIFICATIONS

ACEA E6/E9-16	JASO DH-2	IVECO
ACEA E7/E8/E11-24	RENAULT RLD-3	
API CK-4	VOLVO VDS-4.5	
MAN M3775	MACK EOS-4.5	
DEUTZ DQC IV-18 LA	DAF PSQL 2.1E-LD	
CAT ECF-3	CUMMINS CES 20081/20086	
DETROIT DIESEL DDC 93K218/93K222	DAIMLER DTFR 15C100/110/120	

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 L
200 L
1.000 L
BULK

Edition 11 Date: 05/11/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.