

QUIMIBERICA, S.A.

SAE 10W40 SYNTHETIC 4T MOTORCYCLE



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Oil formulated with synthetic bases guaranteeing high detergent and dispersant power for 4-stroke engines cooled by air or liquid cooling. Recommended for 4-stroke motorcycles. Compatible its use in mopeds without catalytic system, cultivators, lawnmowers, etc.

PROPERTIES

- It protects against corrosion and wear.
- It has antioxidant properties.
- Thanks to its composition, it allows for greater clutch disc performance and gearbox protection.
- Its high viscosity index allows for easy cold starts and high resistance of the lubricating film at high temperatures.

TYPE ANALYSIS

PARAMETER	UNIT	VALUE
Density at 15°C	g/cm ³	0,850
Viscosity at 100°C	cSt	12,5-16,3
Viscosity index	-	160
Flash point	°C	>220
Pour point	°C	-36

The mentioned parameters represent typical values.

SPECIFICATIONS

- JASO MA2
- API SL/CF

STORAGE CONDITIONS AND EXPIRATION DATE

The product does not require special storage measures.


As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

PRODUCT SAFETY

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008.



PACKAGING

1 L

Edition 2 Date: 07/04/2025

Page 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.