

QUIMIBERICA, S.A.

SAE 15W40 STOU



BROOK'S

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Multifunctional lubricant for use in engines, transmissions, wet brake systems and integral hydraulic systems of diesel and gasoline agricultural tractors.

PROPERTIES

- Its additives allow for greater lubricant flow and energy transmission throughout the system to ensure proper operation.
- It reduces wear on cams and liners and prolongs the useful life and durability of the engine.
- It offers high performance and protection in both conventional gearboxes and new variable transmissions for tractors.
- Simplicity in maintenance, a single oil for the entire tractor.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Density at 15°C	g/cm ³	0,865
Viscosity at 100°C	cSt	12,5-16,3
Viscosity index	-	150
Flash point	°C	236
Pour point	°C	-24
TBN	mg KOH/g	11,3

The characteristics mentioned represent typical values.

SPECIFICATIONS

API CE/SF
MIL-L-2104 D
MIL-L-46152 B

FORD M2C 159B
JOHN DEERE J27-J20A
MASSEY FERGUSON M1139

JI CASE
API GL-5
CATERPILLAR TO-2

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 L
50 L
200 L
1.000 L

Edition 7 Date: 29/10/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.