



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Mineral-based lubricant with detergent power for 4-stroke diesel and gasoline engines, for stationary engines, suitable for naturally aspirated and even supercharged diesel engines.

PROPERTIES

- It protects the engine against corrosion because it neutralises the acids formed in the combustion of diesel fuels with different sulphur contents.
- It facilitates lubrication, prevents engine wear and helps maintain its power.
- Its detergent power eliminates the products originating in combustion from the hottest parts of the engine, keeping it clean even after long periods of parking.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Density at 15°C	g/cm ³	0,864
Viscosity at 100°C	cSt	12,5-16,3
Viscosity index	-	103
Flash point	°C	220
Pour point	°C	-24

The characteristics mentioned represent typical values.

SPECIFICATIONS

API CF/SF CCMC D2 CAT TO-2 ALLISON C3

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

5 L
20 L
50 L
200 L
1.000 L

Edition 8 Date: 30/10/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.