

QUIMIBERICA, S.A.

SAE 85W140 E.P.



BROOK'S

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Multigrade extreme pressure lubricant oil for gearboxes and differentials in cars, trucks, buses and agricultural equipment. Extreme pressure oil especially recommended for lubricating hypoid and helical type gearboxes and differentials and under-crankcase gears.

PROPERTIES

- Contains corrosion inhibitors on metals.
- Contains E.P. and anti-wear additives that considerably increase the life of the equipment.
- Good anti-foaming properties, preventing the formation of foams.
- Good demulsifying properties, preventing the formation of emulsions.
- Good antioxidant properties, preventing the oxidation of the oil, preventing the viscosity from increasing and deteriorating.

TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Color	-	Amber
Density at 15°C	g/cm3	0,890
Viscosity at 100°C	cSt	24,0-32,5
Viscosity index	-	>95
Flash point	°C	>220
Pour point	°C	<-9

The characteristics mentioned represent typical values.

SPECIFICATIONS

API GL-5
MIL-L-2105 D

VOLVO 97310
ZF TE-ML 07A/08/16C/16D/21A

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.



PACKAGING

1 L
5 L
20 L
200 L
1.000 L

Edition 6 Date: 04/11/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

Avda. de Cameros, Parc. 183- Tel.:941 25 66 11- Fax: 941 24 15 89-26150 Arrúbal (La Rioja)- SPAIN
quimiberica@quimiberica.es - www.quimiberica.es - ISO 9001 - ISO 14001 - ISO 45001