

QUIMIBERICA, S.A.

SILBRON S.P.F



BROOK'S

TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

SILBRON S.P.F is a self-forming silicone sealant for joints, based on silicone elastomers, which cross-links at room temperature. Use in:

- Joining and replacing cork, cardboard, fibre, etc. joints...
- Sealing joints in extreme temperature conditions
- Bonding and sealing panels, oven doors, smoke outlets, etc...
- Sealing oil pans and water pumps.
- Fixing and sealing in refrigerators and boilers.
- Insulation of electrical conductors, appliances, etc...

PROPERTIES

- Single component, no pre-mixing required.
- Excellent adhesion. No primer or catalyst required.
- Good resistance to ozone and weathering. Does not harden or crack.
- Good resistance to water, antifreeze liquids, diluted inorganic alkalis, oils and diesel fuel and other hydrocarbons, etc.
- Once cured, it produces a non-toxic silicone rubber.
- Curing (drying) time; 3mm / 24 hours.

HOW TO USE

Surfaces must be clean and dry before applying the product, free of dust, sawdust, oil, grease, etc.

Use: drill the head of the tube, screw on the nozzle, cut the nozzle to the required size and make or fill the joint with the product.

The fresh product is removed with an organic solvent. Once cured, it can only be removed mechanically.

During curing, SILBRON S.P.F. is irritating, it emits small amounts of acetic acid, so the work area must be well ventilated.

Use gloves and in case of stains, wash with industrial detergent when the product is still fresh. Hands should not be washed with solvents.

STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 1 year.



PACKAGING

Tube 80 gr

Edition 8 Date: 06/11/2024

Pág. 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.