

# QUIMIBERICA, S.A.

## SINTEX 2T ULTRA XTH



### TECHNICAL INFORMATION

#### DESCRIPTION AND APPLICATION

**100% SYNTHETIC** oil formulated with clean technology, for all types of 2-stroke engines and compatible with catalytic converters. Use in tillers, lawnmowers, motorcycles, mopeds, chainsaws, etc.

#### PROPERTIES

- **LOW SMOKE:** Reduces smoke emissions.
- Facilitates instant start-up.
- Protects pistons, spark plugs and exhausts.
- **Prevents pearl formation.**
- **LOW ASH:** Reduces carbon residue formation: ASH-FREE ADDITIVES.
- Improves combustion and increases power.
- Detergent properties.
- High **lubricating** capacity.
- Deposit control.
- **Cleaner technology:** extended service intervals.

#### TYPE ANALYSIS

PARAMETERS	UNITS	VALUE
Color	-	Bluish green
Density at 15 °C	g/cm3	0,870
Viscosity at 100 °C	cSt	8,50
Viscosity index	-	110
Flash point	°C	125
Pour point	°C	-12

The characteristics mentioned represent typical values.

#### SPECIFICATIONS

JASO FD                      TISI  
API TC                        ISO- L -EGD

#### HOW TO USE

Mix with gasoline, in a dosage of 2%.



#### PACKAGING

1 L (DISP.)  
5 L  
20 L

Edition 6 Date: 30/10/2024

Página 1

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.

# QUIMIBERICA, S.A.

## SINTEX 2T ULTRA XTH



BROOK'S

### TECHNICAL INFORMATION

#### STORAGE CONDITIONS AND EXPIRATION

The product does not require special storage measures.

As general storage conditions, heat sources, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Best before date: 2 years.

Edition 6 Date: 30/10/2024

Página 2

This information is given as a guide and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production, and do not constitute a product specification. Before using the product, it is recommended to read the information contained on the packaging. Quimiberica S.A. products are covered by a legal guarantee (Guarantee Law) against lack of conformity under the provisions of the General Law for the Defence of Consumers and Users (Royal Legislative Decree 21/2007) provided that the storage conditions specified in this technical data sheet are met. This technical data sheet specifies the duration of said product guarantee.